



DUAL
FLIP
I
CORE

FACTORY FINISH	Low (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
HOOK POTENTIAL	Low (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
BREAKPOINT SHAPE	Smooth Arc (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
FLARE POTENTIAL	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
RG - AVERAGE	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
COVER STOCK	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)



DUAL
FLIP
I
CORE

FACTORY FINISH	Low (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
HOOK POTENTIAL	Low (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
BREAKPOINT SHAPE	Smooth Arc (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
FLARE POTENTIAL	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
RG - AVERAGE	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
COVER STOCK	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)



DUAL
FLIP
I
CORE

FACTORY FINISH	Low (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
HOOK POTENTIAL	Low (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
BREAKPOINT SHAPE	Smooth Arc (10)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
FLARE POTENTIAL	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
RG - AVERAGE	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)
COVER STOCK	Low (0)	High (175)	Angular (100)	High (.060)	Cover Heavy (10)

500, 1000, 2000 Siaair Micro Pad

CFL: Uti Max Pearl

High (175)	155
Angular (100)	95
High (.060)	.050
Cover Heavy (10)	4.4

500, 1000, 2000 Siaair Micro Pad

CFL: Uti Max Pearl

High (175)	155
Angular (100)	95
High (.060)	.050
Cover Heavy (10)	4.4

500, 1000, 2000 Siaair Micro Pad

CFL: Uti Max Pearl

High (175)	155
Angular (100)	95
High (.060)	.050
Cover Heavy (10)	4.4

BALL MOTION CHARACTERISTICS

* Skids effortlessly through the front, saving axis rotation in the mid-lane to grab the backend for strong continuous response to friction

LANE CONDITIONS

* medium to medium-oily lane conditions

More Info: bowlwithbrunswick.com
 Flip Cards: bowlingsdisplays.com

BALL MOTION CHARACTERISTICS

* Skids effortlessly through the front, saving axis rotation in the mid-lane to grab the backend for strong continuous response to friction

LANE CONDITIONS

* medium to medium-oily lane conditions

More Info: bowlwithbrunswick.com
 Flip Cards: bowlingsdisplays.com

BALL MOTION CHARACTERISTICS

* Skids effortlessly through the front, saving axis rotation in the mid-lane to grab the backend for strong continuous response to friction

LANE CONDITIONS

* medium to medium-oily lane conditions

More Info: bowlwithbrunswick.com
 Flip Cards: bowlingsdisplays.com