Ultra Low Dual FLip "I" BLOCK Symmetrical Core

FACTORY FINISH		500 Siaair Micro Pad; Rough Buff	
HOOK POTENTIAL	Low (10)	170	High (175)
BREAKPOINT SHAPE	Smooth Arc (10)	85	Angular (100)
FLARE POTENTIAL	Low (0)	.055	High (.060)
RG - AVERAGE	Cover Heavy (1)	3.1	Cover Heavy (10)
COVER STOCK		CFT maxxed-out Solid	

OUT OF THE BOX CHARACTERISTICS

Skids easily through the front, saving axis rotation for the backend with a strong continuous breakpoint.

LANE CONDITIONS

best used on fresh and wet/dry lane conditions where control is needed on medium-oily to oily lane patterns.

More Info: brunswickbowling.com
Talker Cards: bowlingdisplays.com

Ultra Low Dual FLip "I" BLOCK Symmetrical Core

FACTORY FINISH		500 Siaair Micro Pad; Rough Buff	
HOOK POTENTIAL	Low (10)	170	High (175)
BREAKPOINT SHAPE	Smooth Arc (10)	85	Angular (100)
FLARE POTENTIAL	Low (0)	.055	High (.060)
RG - AVERAGE	Cover Heavy (1)	3.1	Cover Heavy (10)
COVER STOCK		CFT maxxed-out Solid	

OUT OF THE BOX CHARACTERISTICS

Skids easily through the front, saving axis rotation for the backend with a strong continuous breakpoint.

LANE CONDITIONS

best used on fresh and wet/dry lane conditions where control is needed on medium-oily to oily lane patterns.

More Info: brunswickbowling.com
Talker Cards: bowlingdisplays.com

Ultra Low Dual FLip "I" BLOCK Symmetrical Core

FACTORY FINISH		500 Siaair Micro Pad; Rough Buff	
HOOK POTENTIAL	Low (10)	170	High (175)
BREAKPOINT SHAPE	Smooth Arc (10)	85	Angular (100)
FLARE POTENTIAL	Low (0)	.055	High (.060)
RG - AVERAGE	Cover Heavy (1)	3.1	Cover Heavy (10)
COVER STOCK		CFT maxxed-out Solid	

OUT OF THE BOX CHARACTERISTICS

Skids easily through the front, saving axis rotation for the backend with a strong continuous breakpoint.

LANE CONDITIONS

best used on fresh and wet/dry lane conditions where control is needed on medium-oily to oily lane patterns.

More Info: brunswickbowling.com
Talker Cards: bowlingdisplays.com