Low Differential I-Block Symmetric

FACTORY FINISH	
HOOK POTENTIAL	Low (10)
BREAKPOINT SHAPE	Smooth Arc (10)
FLARE POTENTIAL	Low (0)
RG - AVERAGE	Cover Heavy (1)
COVER STOCK	

500, 1,500 Siaair Micro Pad

125	High (250)
40	Angular (150)
.030	High (.060)
N/A	Cover Heavy (10)

BTU (Better Than Urethane)

BALL MOTION CHARACTERISTICS

BTU coverstock formulation to produce "urethane" ball motion with improved consistency and enhanced hitting power on high friction lane conditions.

LANE CONDITIONS

ALL

More Info: bowlwithbrunswick.com

Flip Cards:™ bowlingdisplays.com

Low Differential I-Block Symmetric

FACTORY FINISH	
HOOK POTENTIAL	Low (10)
BREAKPOINT SHAPE	Smooth Arc (10)
FLARE POTENTIAL	Low (0)
RG - AVERAGE	Cover Heavy (1)
COVER STOCK	

500, 1,500 Siaair Micro Pad

125	High (250)
40	Angular (150)
.030	High (.060)
N/A	Cover Heavy (10)

BTU (Better Than Urethane)

BALL MOTION CHARACTERISTICS

BTU coverstock formulation to produce "urethane" ball motion with improved consistency and enhanced hitting power on high friction lane conditions.

LANE CONDITIONS

ALL

More Info: bowlwithbrunswick.com

Flip Cards:™ bowlingdisplays.com

Low Differential I-Block Symmetric

FACTORY FINISH	
HOOK POTENTIAL	Low (10)
BREAKPOINT SHAPE	Smooth Arc (10)
FLARE POTENTIAL	Low (0)
RG - AVERAGE	Cover Heavy (1)
COVER STOCK	

500, 1,500 Siaair Micro Pad

125	High (250)
40	Angular (150)
.030	High (.060)
N/A	Cover Heavy (10)

BTU (Better Than Urethane)

BALL MOTION CHARACTERISTICS

BTU coverstock formulation to produce "urethane" ball motion with improved consistency and enhanced hitting power on high friction lane conditions.

LANE CONDITIONS

ALL

More Info: bowlwithbrunswick.com

Flip Cards:™ bowlingdisplays.com