





FACTORY FINISH	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)
HOOK POTENTIAL	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)
BREAKPOINT SHAPE	Smooth Arc (10)	Angular (100)	Smooth Arc (10)	Angular (100)	Smooth Arc (10)	Angular (100)	Smooth Arc (10)	Angular (100)	Smooth Arc (10)	Angular (100)
FLARE POTENTIAL	Low (0)	High (1.060)	Low (0)	High (1.060)	Low (0)	High (1.060)	Low (0)	High (1.060)	Low (0)	High (1.060)
RG - AVERAGE	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)	Cover Heavy (1)
COVER STOCK	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)	Low (10)	High (175)



BALL MOTION CHARACTERISTICS
 Projects easily through the front and mid-lane with a very quick response to friction on the backend creating a highly angular motion that rips through the pins.
LANE CONDITIONS
 medium oily to oily lane
 More info: dvwbowling.com
 Flip Cards: bowlingdisplays.com

BALL MOTION CHARACTERISTICS
 Projects easily through the front and mid-lane with a very quick response to friction on the backend creating a highly angular motion that rips through the pins.
LANE CONDITIONS
 medium oily to oily lane
 More info: dvwbowling.com
 Flip Cards: bowlingdisplays.com

BALL MOTION CHARACTERISTICS
 Projects easily through the front and mid-lane with a very quick response to friction on the backend creating a highly angular motion that rips through the pins.
LANE CONDITIONS
 medium oily to oily lane
 More info: dvwbowling.com
 Flip Cards: bowlingdisplays.com